


## Product Designation

<b>Product Group:</b>	Habasit Cleandrive monolithic conveyor belts
<b>Product Sub-Group:</b>	Flat conveyor belts
<b>Main Industry Segments:</b>	Dairies; Fruit; Meat; Poultry; Vegetables
<b>Belt Applications:</b>	General conveying belt
<b>Special Features:</b>	Abrasion resistant on both sides; Easy cleanability; Hygienic
<b>Mode of Use/Conveyance:</b>	Horizontal

## Product Design (enlarged)



## Product Construction/Design

<b>1 Conveying Side (Material):</b>	Thermoplastic polyurethane (TPU)
<b>1 Conveying Side (Surface):</b>	Smooth
<b>1 Conveying Side (Property):</b>	Adhesive
<b>1 Conveying Side (Color):</b>	Cobalt blue
<b>2 Traction Layer (Material):</b>	Aramide cords
<b>Number of Fabrics:</b>	
<b>3 Running Side/Pulley Side (Material):</b>	Thermoplastic polyurethane (TPU)
<b>3 Running Side/Pulley Side (Surface):</b>	Glossy
<b>3 Running Side/Pulley Side (Color):</b>	Cobalt blue

## Product Characteristics

<b>Slider bed suitable:</b>	No
<b>Carrying rollers suitable:</b>	Yes
<b>Troughed installation suitable:</b>	Yes
<b>Power turns, curved installations:</b>	No
<b>Nosebar suitable:</b>	No
<b>Low noise applications:</b>	No
<b>Antistatically equipped:</b>	No
<b>Metal detector suitable:</b>	Yes
<b>Flammability:</b>	No specific flammability prevention property
<b>Food suitability FDA:</b>	Yes - acc. to 21CFR parts 170 - 199. Contact your Habasit representative for detailed information.
<b>Food suitability USDA:</b>	No use intended
<b>Food suitability EU:</b>	Yes - acc. to Regulation (EC) No. 1935/2004 and Regulation (EU) No 10/2011 as amended. Contact your Habasit representative for detailed information.

## Technical Data

<b>Thickness:</b>	2 mm	0.08 in.
<b>Mass of belt (belt weight):</b>	2.4 kg/m <sup>2</sup>	0.49 lbs./sq.ft
<b>Nosebar Radius (minimum):</b>	NA mm	NA in.
<b>Pulley diameter (minimum):</b>	25 mm	1 in.
<b>Pulley diameter minimum with counter flexion:</b>	25 mm	1 in.
<b>Tensile force for 1% elongation (k1% static) per unit of width (Habasit Standard SOP3-155 / EN ISO21181):</b>	8.5 N/mm	49 lbs./in.
<b>Tensile force for 1% elongation after relaxation (k1% relaxed) per unit of width (Habasit Standard SOP3-155 / EN ISO 21181):</b>	6.5 N/mm	37 lbs./in.
<b>Admissible tensile force per unit of width:</b>	6 N/mm	34 lbs./in.
<b>Operating temperature admissible (continuous):</b>	Min -20 °C Max 80 °C	Min -4 °F Max 176 °F
<b>Coefficient of friction on slider bed of pickled steel sheet:</b>	[-]	[-]
<b>Seamless manufacturing width:</b>	609 mm	24 in.

All data are approximate values under standard climatic conditions: 23°C/73°F, 50% relative humidity (DIN 50005/ISO 554), and are based on the Master Joining Method.

## Additional Technical Information

<b>Chemical Resistance Class:</b>	6 (These indications are not guarantees of properties)
<b>Installation and Handling Instructions:</b>	Install the slack belt and tension until running perfectly under the full belt load.
<b>Limitations:</b>	This product has not been tested according to ATEX standards (atmospheres with explosion risk - ATEX 95 regulation or EU directive 94/9) and therefore is subject to user's analysis in the respective environment.

## Storage

For details consult 'Storage and handling requirements for belts and machine tapes' or contact Habasit. Protect belts from sunlight/UV-radiation/dust and dirt. Store spare belts in a cool and dry place and if possible in their original packaging.

## Legend

	German federal institute for risk assessment (Bundesinstitut fuer Risikobewertung)
<b>EEC</b>	European Economic Community
<b>EU</b>	European Union (Directive 2002/72/EC)
<b>FDA</b>	Food and Drug Administration
<b>NA</b>	Not available
<b>NAP</b>	Not applicable
<b>USDA</b>	United States Department of Agriculture (Food Safety and Inspection Service, Washington D.C.)

## Disclaimer

### Product Application Disclaimer (valid for ALL Habasit products and mentioned on all PDS)

This disclaimer is made by and on behalf of Habasit and its affiliated companies, directors, employees, agents and contractors (hereinafter collectively "HABASIT") with respect to the products referred to herein (the "Products"). SAFETY WARNINGS SHOULD BE READ CAREFULLY AND ANY RECOMMENDED SAFETY PRECAUTIONS BE FOLLOWED STRICTLY! Please refer to the Safety Warnings herein, in the Habasit catalogue as well as installation and operating manuals. All indications / information as to the application, use and performance of the Products are recommendations provided with due diligence and care, but no representations or warranties of any kind are made as to their completeness, accuracy or suitability for a particular purpose. The data provided herein are based on laboratory application with small-scale test equipment, running at standard conditions, and do not necessarily match product performance in industrial use. New knowledge and experience may lead to re-assessments and modifications within a short period of time and without prior notice. EXCEPT AS EXPLICITLY WARRANTED BY HABASIT, WHICH WARRANTIES ARE EXCLUSIVE AND IN LIEU OF ALL OTHER WARRANTIES, EXPRESS OR IMPLIED, THE PRODUCTS ARE PROVIDED "AS IS". HABASIT DISCLAIMS ALL OTHER WARRANTIES, EITHER EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, IMPLIED WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE, NON-INFRINGEMENT, OR ARISING FROM A COURSE OF DEALING, USAGE, OR TRADE PRACTICE, ALL OF WHICH ARE HEREBY EXCLUDED TO THE EXTENT ALLOWED BY APPLICABLE LAW. BECAUSE CONDITIONS OF USE IN INDUSTRIAL APPLICATION ARE OUTSIDE OF HABASIT'S CONTROL, HABASIT DOES NOT ASSUME ANY LIABILITY CONCERNING THE SUITABILITY AND PROCESS ABILITY OF THE PRODUCTS, INCLUDING INDICATIONS ON PROCESS RESULTS AND OUTPUT.