


Product Designation

Product Group:	Hamid machine tapes
Main Industry Segments:	Folding; Paper converting; Paper manufacturing and processing; Paper printing and finishing
Belt Applications:	Folder belt; Paper handling belt; Processing belt
Special Features:	Abrasion resistant; Adhesive-free joint; Constant grip and release property; Dimensionally stable; Non-marking
Mode of Use/Conveyance:	Horizontal; Inclined; Vertical

Product Design (enlarged)



Product Construction/Design

1 Conveying Side (Material):	Polyurethane cross-linked (PUR)
1 Conveying Side (Surface):	Impregnated fabric
1 Conveying Side (Property):	Non-adhesive
1 Conveying Side (Color):	Black
2 Traction Layer (Material):	Polyamide (PA) fabric /Thermoplastic polyurethane (TPU) foil
Number of Fabrics:	2
3 Running Side/Pulley Side (Material):	Acrylonitrile-Butadiene-Rubber (NBR)
3 Running Side/Pulley Side (Surface):	Fine textile structure
3 Running Side/Pulley Side Property:	Fine textile structure
3 Running Side/Pulley Side (Color):	Green

Product Characteristics

Slider bed suitable:	No
Carrying rollers suitable:	Yes
Troughed installation suitable:	No
Antistatically equipped:	Yes

Technical Data

Thickness:	1.45 mm	0.06 in.
Mass of belt (belt weight):	1.6 kg/m ²	0.33 lbs./sq.ft
Pulley diameter minimum without or with counter flecion:	25 mm	1 in.
Tensile force for 1% elongation (k1% static) per unit of width (Habasit Standard SOP3-155 / EN ISO21181):	4.8 N/mm	27 lbs./in.
Tensile force for 1% elongation after relaxation (k1% relaxed) per unit of width (Habasit Standard SOP3-155 / EN ISO 21181):	1.7 N/mm	10 lbs./in.
Operating temperature admissible (continuous):	Min -20 °C Max 60 °C	Min -4 °F Max 140 °F
Coefficient of friction of driving pulley of steel:	0.7 [-]	0.7 [-]
Seamless manufacturing width:	1200 mm	47 in.

All data are approximate values under standard climatic conditions: 23°C/73°F, 50% relative humidity (DIN 50005/ISO 554), and are based on the Master Joining Method.

Additional Technical Information

Chemical Resistance Class:	2 (These indications are not guarantees of properties)
Installation and Handling Instructions:	Do not go below initial elongation (epsilon) ~0.5%.; Install the slack belt and tension until running perfectly under the full belt load.
Limitations:	Keep belt edges free of any installation/machine contact; This product has not been tested according to ATEX standards (atmospheres with explosion risk - ATEX 95 regulation or EU directive 94/9) and therefore is subject to user's analysis in the respective environment.

Storage

For details consult 'Storage and handling requirements for belts and machine tapes' or contact Habasit. Protect belts from sunlight/UV-radiation/dust and dirt. Store spare belts in a cool and dry place and if possible in their original packaging.

Legend

*	No calculation Value
2)	Product containing different coating materials such as elastomer, natural fibers, silicones, etc., are not subject to the directive 2002/72/EC
3)	CLA: Coordination of the centre line-average value Ra (in the US also Arithmetical Average (AA)) to the maximum peak to valley height Rt for surfaces manufactured by chip removal.
8)	Due to high coefficient of friction of running/pulley side, the suitability for use on slider beds is limited German federal institute for risk assessment (Bundesinstitut fuer Risikobewertung)
EEC	European Economic Community
EU	European Union (Directive 2002/72/EC)
FDA	Food and Drug Administration
NA	Not available
NAP	Not applicable
USDA	United States Department of Agriculture (Food Safety and Inspection Service, Washington D.C.)

Disclaimer

Product Application Disclaimer (valid for ALL Habasit products and mentioned on all PDS)

This disclaimer is made by and on behalf of Habasit and its affiliated companies, directors, employees, agents and contractors (hereinafter collectively "HABASIT") with respect to the products referred to herein (the "Products").
SAFETY WARNINGS SHOULD BE READ CAREFULLY AND ANY RECOMMENDED SAFETY PRECAUTIONS BE FOLLOWED STRICTLY! Please refer to the Safety Warnings herein, in the Habasit catalogue as well as installation and operating manuals. All indications / information as to the application, use and performance of the Products are recommendations provided with due diligence and care, but no representations or warranties of any kind are made as to their completeness, accuracy or suitability for a particular purpose. The data provided herein are based on laboratory application with small-scale test equipment, running at standard conditions, and do not necessarily match product performance in industrial use. New knowledge and experience may lead to re-assessments and modifications within a short period of time and without prior notice.

EXCEPT AS EXPLICITLY WARRANTED BY HABASIT, WHICH WARRANTIES ARE EXCLUSIVE AND IN LIEU OF ALL OTHER WARRANTIES, EXPRESS OR IMPLIED, THE PRODUCTS ARE PROVIDED "AS IS". HABASIT DISCLAIMS ALL OTHER WARRANTIES, EITHER EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, IMPLIED WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE, NON-INFRINGEMENT, OR ARISING FROM A COURSE OF DEALING, USAGE, OR TRADE PRACTICE, ALL OF WHICH ARE HEREBY EXCLUDED TO THE EXTENT ALLOWED BY APPLICABLE LAW. BECAUSE CONDITIONS OF USE IN INDUSTRIAL APPLICATION ARE OUTSIDE OF HABASIT'S CONTROL, HABASIT DOES NOT ASSUME ANY LIABILITY CONCERNING THE SUITABILITY AND PROCESS ABILITY OF THE PRODUCTS, INCLUDING INDICATIONS ON PROCESS RESULTS AND OUTPUT.